

AQUAPHOR PROFESSIONAL

water treatment

*The unique features of APRO Series systems
allow a consistently production
of high quality water for your specific application*

We introduce APRO Reverse Osmosis product line

Equipped with the highest quality components

Robust construction and easy maintenance

New design and quiet operation

Built and assembled in Estonia (EU)



L.Tolstoi 2A , Sillamae

40231 Estonia

www.pro.aquaphor.com

e-mail: pro.sales@aquaphor.com



Standard features – APRO 125-375

Model	APRO 125	APRO 250	APRO 375
Membrane Size (inch)	2.5X40	2.5X40	2.5X40
Salt rejection (%)	95-99	95-99	95-99
Recovery rate (%)	50	50	50
Membrane Quantity	1	2	3
Permeate Flow (LPH)	125	250	375
Max inlet TDS (ppm)	4,000	4,000	4,000

*Please contact us with any water quality.

BENEFITS

- Improved water quality
- Extended membrane life
- Low maintenance operation
- Space saving design
- Quiet operation
- Reduced operational costs

OPTIONAL FEATURES

- Antiscalant dosing pumps
- Supply pumps and storage vessels
- UF pre-treatment
- Polish DI tanks

MATERIAL STRUCTURE

- Various Product Sizes 125 – 375 LPH
- Stainless steel Frame
- Multi Stage Stainless steel “Grundfos” pump
- MP controller for quality monitoring
- High rejection TFC Membranes
- Panel mounted Glycerin-filled Gauges
- Low Pressure Shutoff
- Double Pre-filter
- High Pressure Stainless steel piping
- Low Pressure PVC piping

